

Ficha Técnica del Producto

DOWNLIGHT LED **ADWLED CR**

ILD.CR



Downlight Led empotrable

Potencia: 6/12/18/20W

Flujo lumínico: 430/970/1270/1480lm*

Temperatura de color 4000K

Disponibles en blanco o en gris*

Formato Redondo (-R-) o Cuadrado (-C-)*

*Ver tabla.

		P(W)	Flujo (Lm)
ILD6.CR.R.14	ADWLED CR 6W R 4000K BLANCO	6	430
ILD6.CR.R.24	ADWLED CR 6W R 4000K GRIS	6	430
ILD12.CR.R.14	ADWLED CR 12W R 4000K BLANCO	12	970
ILD12.CR.R.24	ADWLED CR 12W R 4000K GRIS	12	970
ILD18.TR.R.14	ADWLED TR 18W R 4000K BLANCO	18	1270
ILD20.CR.R.14	ADWLED CR 20W R 4000K BLANCO	20	1480
ILD20.CR.R.24	ADWLED CR 20W R 4000K GRIS	20	1480
ILD6.CR.C.14	ADWLED CR 6W C 4000K BLANCO	6	430
ILD6.CR.C.24	ADWLED CR 6W C 4000K GRIS	6	430
ILD12.CR.C.14	ADWLED CR 12W C 4000K BLANCO	12	970
ILD12.CR.C.24	ADWLED CR 12W C 4000K GRIS	12	970
ILD20.CR.C.14	ADWLED CR 20W C 4000K BLANCO	20	1480

ILD6.CR.R

Downlight redondo 120x22mm; Corte: 110mm

ILD12.CR.R

Downlight redondo 173x22mm; Corte: 155mm

ILD18.CR.R

Downlight redondo 225mm; Corte: 205mm.

ILD20.CR.R

Downlight redondo 225x22mm; Corte: 205mm

ILD6.CR.C

Downlight cuadrado 120x120x22mm; Corte: 110x110mm

ILD12.CR.C

Downlight cuadrado 173x173x22mm; Corte: 155x155mm

ILD20.CR.C

Downlight cuadrado 225x225x22mm; Corte: 205x205mm